

## PROLAKE<sup>5</sup> 85 For impoundments up to 7 acres

- Fracking Pond Applications
- Delivers Over 8 CFM 24/7
- Utilizes Tough Dual Duraplate<sup>™</sup> Diffusers
- Rugged Design To Withstand Harsh Environments

## **Impoundment Package Features**

6.17 HP Oilless Regenerative Blower 85 CFM Open Flow 9.5Y Amps Start@460V 460/60/3 Maximum 325" Water Column Differential Pressure Outlet Adapter With Pressure Relief Valve Blow-Off Valve Flexible High Temperature Vibration Isolator Hose Inlet Fitting Includes Industrial Air Filter With Replaceable Element Electrical Panel/NEMA Outdoor Rated Manual Motor Starters TEFC Motor Class F Insulation UL Listed

40' Galvanized Metal Compressor Outlet Air Pipe - 2" (For Heat Dissipation With Appropriate Fittings To Hairpin & Connection To Blower)

Up To 10 Dual Duraplate<sup>™</sup> Air Diffusers Depending On Final Size

Between 6,000 To 10,000 Feet Of 3/4" Alpine™ Weighted Airline Depending On Final Size

Between 1200 To 1500 Feet Of 3/4" Gates Adaptaflex Tubing Depending On Final Size



6.17HP Oilless Regenerative Blower



Duraplate<sup>™</sup> Dual Diffuser



Alpine<sup>™</sup> 3⁄4" Weighted Airline



Black ¾" Adapaflex™ Airline



40' Galvanized Metal Compressor Outlet Air Pipe - 2"

## **Product Notes**

Electrical panel and blower rated for outdoor installation, blower mounted on galvanized steel pallet all-welded construction outdoor/industrial rated, ready to set and connect. Control panel shipped loose for site installation on power pedestal by customer's electrician. System includes fittings and clamps to install 3/4" Alpine<sup>™</sup> Weighted Tubing and Diffusers. Includes clamps and fittings to connect 3/4" Adaptaflex to 3/4 Alpine<sup>™</sup> Self Weighted Tubing at toe of berm (in most cases). Installation, customer to provide 2" End Welded Air Distribution Trunk Manifold and 3/4" Airflow Adjustment (Ball) Valves (Qty. 20) with Male Adapter (3/4" Npt X 3/4" Spiral Barb) for each Airflow Outlet on Trunk Manifold.



## PROLAKE<sup>5</sup> 85 FOR IMPOUNDMENTS UP TO 7 ACRES

- Fracking Pond Applications
- Delivers Over 8 CFM 24/7
- Utilizes Tough Dual Duraplate<sup>™</sup> Diffusers
- Rugged Design To Withstand Harsh Environments

